

Product Code: SFSS143PL

Description: 3 Gang Unfurnished Dimmer Plate- 3 Apertures



General Information

Insert Dimensions (mm)	142.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)	146 (W) x 86 (H) x 4 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Screwless Complete	
Finish	Stainless Steel	
Compatible Cover Plate	SCP243#	
Materials	Cover Plate: Stainless Steel	Insert: Polycarbonate
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

Compatible Dimmer Modules

MD9014: 100W Dual Mode LED Dimmer Module
MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module
MD9010: 1-10V Analogue Rotary Dimmer Module
MD9022: 40-250W Leading Edge Dimmer Module
MD9042: 60-400W Leading Edge Dimmer Module