

**Product Code:** SFPW660

**Description:** 20A Double Pole 1 Gang Plate Key Lockable Switch



### General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless Complete	
Finish	Polar White	
Compatible Cover Plate	SCP660#	
Materials	Cover Plate: Polycarbonate Earth Plate & Yoke: Mild Steel Terminal Screws: Steel & Yellow Passivated	Insert: Polycarbonate Terminals: Brass GridPro Module: GM2018PW
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Modular Rocker Switches	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	On & Off	
Minimum Back Box Depth (mm)	47	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

**Standards** BS EN 60669-1

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Two keys provided (Spare keys available: SP660)  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.