

Product Code: SFSS504PW

Description: 50A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet



General Information

| | | |
|--|--|---|
| Insert Dimensions (mm) | 142.5 (W) x 82.5 (H) x 2.5 (D) | |
| Plate Dimensions (mm) | 146 (W) x 86 (H) x 4 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| Style | Screwless Complete | |
| Finish | Stainless Steel | |
| Insert Colour | Polar White | |
| Compatible Cover Plate | SCP204# | |
| Materials | Cover Plate: Stainless Steel Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass | Insert: Polycarbonate Switch Cover: Stainless Steel Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 50 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø6 | Terminal Torque Value (Nm) 2.5 |
| Terminal Capacity - Solid (mm²) | 1 x 16 | |
| Double Pole Switch | Yes | |
| Twin Earth Terminals | Yes | |
| Product Marking | Cooker | |
| Minimum Back Box Depth (mm) | 47 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS 4177

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.