

Product Code: SFCH553BK

Description: 13A Ingot Fused Connection Unit With Neon & Optional Flex Outlet



### General Information

|  |  |  |
|--|--|--|
| Insert Dimensions (mm)                 | 82.5 (W) x 82.5 (H) x 2.5 (D)              |  |
| Plate Dimensions (mm)                  | 86 (W) x 86 (H) x 4 (D)                    |  |
| Plate Fixing Centres - Horizontal (mm) | 60.3                                       |  |
| Style                                  | Screwless Complete                         |  |
| Finish                                 | Polished Chrome                            |  |
| Insert Colour                          | Black                                      |  |
| Compatible Cover Plate                 | SCP153#                                    |  |
| Materials                              | Cover Plate: Stainless Steel               | Insert: Polycarbonate                  |
|  | Rear Housing: Urea                         | Fuse Drawer Cover: Stainless Steel     |
|  | Neon Lens: Polycarbonate                   | Terminals: Brass                       |
|  | Terminal Screws: Steel & Yellow Passivated | Internal Busbars: Formed Pressed Brass |
|  | Earth Strap: Mild Steel                    |  |
| Anti Microbial Certified               | No   |  |
| Rated Voltage (V~) (Ue)                | 250  | Frequency (Hz) 50                      |
| Resistive Load Rating (A)              | 13   |  |
| Fuse Fitted Rating & Type              | 13A (BS 1362)                              |  |
| Termination Type                       | Screw                                      |  |
| Terminal Size (mm)                     | Ø5   | Terminal Torque Value (Nm) 2           |
| Terminal Capacity - Solid (mm²)        | 3 x 2.5 or 2 x 4                           |  |
| Switched                               | No   |  |
| Twin Earth Terminals                   | Yes  |  |
| Neon Indicator                         | Yes  | Indicator Colour Red                   |
| Product Marking                        | Fused                                      |  |
| Flex Outlet Available                  | Yes  |  |
| Flex Outlet Location                   | Front of Plate                             | Flex Outlet Dimension (mm) Ø10         |
| Minimum Back Box Depth (mm)            | 35   |  |
| Ingress Protection                     | IP20                                       |  |
| Operational Temperature (°C)           | -5 to +40                                  |  |
| Warranty (Years)                       | 10   |  |
| Standards                              | BS 1363-4<br>BS 1362                       |  |

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.