

Product Code: SFMB660

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch



General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless Complete		
Finish	Metal Black (RAL 9017)		
Compatible Cover Plate	SCP660#		
Materials	Cover Plate: Stainless Steel	Insert: Polycarbonate	
	Earth Plate & Yoke: Mild Steel	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	GridPro Module: GM2018PW	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20	Terminal Torque Value (Nm)	
Termination Type	Screw		
Terminal Size (mm)	Ø5	1.2	
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Modular Rocker Switches	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	On & Off		
Minimum Back Box Depth (mm)	47		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Two keys provided (Spare keys available: SP660)
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.