

Product Code: SFMW164

Description: 4 Gang 2 Way 100W Dimmer Switch



### General Information

Insert Dimensions (mm)	142.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)	146 (W) x 86 (H) x 4 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Screwless Complete	
Finish	Metal White	
Compatible Cover Plate	SCP244#	
Materials	Cover Plate: Stainless Steel	Insert: Polycarbonate
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	PCB: Mixed Components
	Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Load Rating (W)	5 - 100	
Load Rating Comments	Suitable For LED	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.25
Terminal Capacity - Solid (mm²)	2 x 1.5	
2 Way Switch	Yes	
Switch Control Type	Press - ON/OFF, Rotate - Dim	
Dimmer Technology Type	Trailing Edge	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	Warranty - Electronics (Years) 1
Standards	BS EN 60669-1 BS EN 60669-2-1 BS EN 55015 BS EN 61000-3-2	

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

### Compatible Dimmer Modules

MD9014: 100W Dual Mode LED Dimmer Module  
MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module  
MD9010: 1-10V Analogue Rotary Dimmer Module  
MD9022: 40-250W Leading Edge Dimmer Module  
MD9042: 60-400W Leading Edge Dimmer Module