

Product Code: SFBS1535BK

Description: 13A Ingot 1 Gang Double Pole Switched Safety Shutter Socket Outlet



General Information

| | | |
|--|--|--|
| Insert Dimensions (mm) | 82.5 (W) x 82.5 (H) x 2.5 (D) | |
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 4 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Screwless Complete | |
| Finish | Brushed Stainless | |
| Insert Colour | Black | |
| Compatible Cover Plate | SCP835# | |
| Materials | Cover Plate: Stainless Steel | Insert: Polycarbonate |
| | Rear Housing: Urea | Switch Cover: Stainless Steel |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated |
| | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass |
| | Earth Strap: Mild Steel | |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 13 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 2 |
| Terminal Capacity - Solid (mm²) | 3 x 2.5 or 2 x 4 | |
| Double Pole Switch | Yes | |
| 3 Pin Safety Shuttered | Yes | |
| Minimum Back Box Depth (mm) | 35 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

