

**Product Code:** SFCH170BK

**Description:** Non-Isolated Satellite & Non-Isolated Coaxial Outlet



## General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless Complete	
Finish	Polished Chrome	
Insert Colour	Black	
Compatible Cover Plate	SCP232#	
Materials	Cover Plate: Stainless Steel	Insert: Polycarbonate
	Earth Plate: Mild Steel	Terminals: Brass
Anti Microbial Certified	No	
Termination Type	Screw	
Isolated	No	
Non-Isolated	Yes	
Non-Isolated Comments	Enables 2 way signal transmission	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

