

Product Code: SFMW022PW

Description: 20A Double Pole Plate Switch With Optional Flex Outlet



General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless Complete		
Finish	Metal White		
Insert Colour	Polar White		
Compatible Cover Plate	SCP322#		
Materials	Cover Plate: Stainless Steel Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass		
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250		
Resistive Load Rating (A)	20		
Termination Type	Screw		
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm²)	3 x 2.5		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Insert: Polycarbonate
Terminals: Brass
Contacts: Silver "on-lay" Copper / Brass
Earth Strap: Mild Steel

Frequency (Hz) 50

Terminal Torque Value (Nm) 1.8

Flex Outlet Dimension (mm) Ø10

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.