

Product Code: SFBK660

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch



General Information

| | | |
|--|--|---|
| Insert Dimensions (mm) | 82.5 (W) x 82.5 (H) x 2.5 (D) | |
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 4 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Screwless Complete | |
| Finish | Matt Black (RAL 9011) | |
| Compatible Cover Plate | SCP660# | |
| Materials | Cover Plate: Polycarbonate Earth Plate & Yoke: Mild Steel Terminal Screws: Steel & Yellow Passivated | Insert: Polycarbonate Terminals: Brass GridPro Module: GM2018PW |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 20 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 1.2 |
| Terminal Capacity - Solid (mm²) | 3 x 2.5 or 2 x 4 | |
| Modular Rocker Switches | Yes | |
| Double Pole Switch | Yes | |
| Twin Earth Terminals | Yes | |
| Product Marking | On & Off | |
| Minimum Back Box Depth (mm) | 47 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Two keys provided (Spare keys available: SP660)
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.