

essentials

CLICK[®]
ScolmoreGROUP



Weatherproof Switches & Switch Enclosures



A comprehensive selection of weatherproof electrical accessory products.

The polycarbonate construction makes the Aquip66 range a durable and long lasting heavy duty range of products.

AQUIP66[®]

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB

Telephone: 01827 63454

E-mail: sales@scolmore.com, technical@scolmore.com

Facsimile: 01827 63362

Website: www.scolmore.com

Weatherproof Switches & Switch Enclosures

Product Range

Weatherproof Switches & Switch Enclosures

OA411AG	1 Gang 2 Way Switch - IP66 Enclosure - Anthracite Grey
OA412AG	2 Gang 2 Way Switch - IP66 Enclosure - Anthracite Grey
OA401AG	1 Gang Switch IP66 Unfurnished Enclosure - Anthracite Grey
OA402AG	2 Gang Switch IP66 Unfurnished Enclosure - Anthracite Grey



OA411AG, OA401AG




OA412AG, OA402AG


Weatherproof Switches & Switch Enclosures

Product Dimensional Drawings (mm)

Weatherproof Switches & Switch Enclosures



OA411AG, OA401AG



OA412AG, OA402AG

Weatherproof Switches & Switch Enclosures**Technical Specification****Weatherproof Switches & Switch Enclosures**

Material Composition	IP66 Enclosure: Polycarbonate, Rubber Gasket, Brass Lugs, Silicone Membrane Switches: Urea Rocker , Nylon Housing, Brass Terminals Silver “on-lay” copper/brass contacts Steel and Yellow Passivated Terminal Screws
MiniGrid Modules	Single Width
Cable Size (411,412)	4 x 1.5mm ² or 2 x 2.5mm ²
Cable Entry	20mm Knockouts (1 top/bottom, 2 either side & 1 in rear)
UV Stabilised Enclosure	Yes
Ingress Protection	IP66
Warranty	5 Years (Domestic)
Standards	EN 60669-1: 1999 + A1: 2002 + A2: 2008 BS EN 60529: 1992 + A2: 2013

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Supplied complete with rubber gasket which helps maintain the IP rating when installing on to uneven walls.

Both 1 gang and 2 gang Aquip switches and unfurnished switch enclosures utilise MiniGrid 13A/10AX Switch Modules as standard.



EU DECLARATION OF CONFORMITY

1. *Issuer Name* Scolmore International Limited
2. *Issuer Address* 1 Scolmore Park, Landsberg,
Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7XB
3. *Object(s) of Declaration* Aquip66 Range
- a. *Group* Switches & Switch Enclosures
- b. *Models No.* OA411AG, OA412AG, OA401AG, OA402AG
4. *The object of the declaration described above is in conformity with the requirements of the following Legislations:*

Document No	Title
2014/30/EC	EMC Directive
2014/35/EC	Low Voltage Directive

5. *All products contained within the aforementioned comply with the relevant standards and requirements listed below.*

EN 60669-1:1999 + A1:2002 + A2:2008
BS EN 60529: 1992 + A2: 2013

6. *I hereby declare that the equipment named above has been designed to comply with the relevant sections of the above referenced specifications. The unit complies with all applicable Essential Requirements of the Directives.*

In conjunction with the above all manufacture and process controls are in accordance with ISO 9001:2015.

This declaration has been issued under the sole responsibility of the manufacturer, signed at, for and on behalf of: Scolmore International Limited



Karl Rawlins – Senior Technical Support Engineer