



Flow Ceiling Rose & Cover



With the emphasis on flexibility and ease of installation, many building design projects are now focusing on products and services that can adapt to changing legislation, energy efficiency and the ever changing needs of the client. Flexibility is important as requirements can change and the ability to gain additional outputs quickly to adapt to these changes are seen as an advantage.

Flow Ceiling Rose & Cover

Product Range

Flow Ceiling Rose & Cover

CT1400

250V~ 20A Click Flow Ceiling Rose

CT1401

Click Flow Ceiling Rose Cover




CT1400



CT1401

Product Dimensional Drawings (mm)



V1.0

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB

Telephone: 01827 63454

E-mail: sales@scolmore.com, technical@scolmore.com

Facsimile: 01827 63362

Website: www.scolmore.com



Flow Ceiling Rose & Cover

Technical Specification

Flow Ceiling Rose & Cover

Material Composition	Ceiling Rose: Polycarbonate
	Ceiling Rose Cover: Polycarbonate
	Female Module: Nylon PA66
	Terminals: HPb59-1 (CU 59%) Silver Plated
	Terminal Screws: Steel and Yellow Passivated
Voltage	250V~ 50Hz
Current Rating	20A Max
Terminal Conductor Sizes	Up to 3 x 2.5mm ² T&E
Compatible Connectors	CT101C - 3 Pin Connector
	CT102C - 3 Pin Connector (Screw Cable Clamps)
	CT103C - 3 Pin Connector (Fast-fit Cable Clamps)
	CT202C - 4 Pin Connector (Screw Cable Clamps)
	CT203C - 4 Pin Connector (Fast-fit Cable Clamps)
	(CT1401 not suitable for use with CT103M & CT203M)
Warranty	10 Years
IP Rating	IP20
Operational Temperature	-5° to +40°C
Standards	KEMA-KEUR
	BS 5733 : 2010 + A1 : 2014 (CT300)
	BS 8488 : 2009 + A1 : 2010 (CT350)
	IEC EN 61535 : 2009 + A1: 2013 + C1: 2014

Errors & Omissions excluded. Specification is subject to change without notice. Pre-Fabricated wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufacturers installation coupler systems is not automatically prevented by compliance with IEC 61535.

V1.0

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB

Telephone: 01827 63454

E-mail: sales@scolmore.com, technical@scolmore.com

Facsimile: 01827 63362

Website: www.scolmore.com



Scolmore International Ltd

1 Scolmore Park: Landsberg
Lichfield Road Industrial Estate
Tamworth, Staffordshire B79 7XB

t: 01827 63454

f: 01827 63362

e: sales@scolmore.com

w: www.scolmore.com

DECLARATION OF CONFORMITY

1. *Issuer Name* Scolmore International Limited
2. *Issuer Address* 1 Scolmore Park, Landsberg,
Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7XB
3. *Object(s) of Declaration* The Flow Range
 - a. *Group* Ceiling Rose & Covers
 - b. *Models No.* CT1400, CT1401
4. *The object of the declaration described above is in conformity with the requirements of the following Certification Mark*

KEMA-KEUR

5. *All products contained within the aforementioned comply with the relevant standards and requirements listed below.*

BS 5733 : 2010 + A1 : 2014

BS 8488 : 2009 + A1 : 2010

IEC EN 61535: 2009 + A1: 2013 + C1:2014

6. *I hereby declare that the equipment named above has been designed to comply with the relevant sections of the above referenced specifications. The unit complies with all applicable Essential Requirements of the Directives.*

In conjunction with the above all manufacture and process controls are in accordance with ISO 9001:2008

Signed, for and on behalf of: Scolmore International Limited

Steven Bettson BSc - Senior Technical Support Engineer

CE 14