

SPECIFICATION SHEET

Product Code GM2003*

Description 20AX 2 Way Key Switch Module



General Information	
Finishes Available	Replace * with: PW (Polar White), BK (Black), BKCH, PWCH (Chrome), BKSC, PWSC (Satin Chrome), PWBR, BKBR (Brass), BKBN (Black Nickel), BKPN, PWPB (Pearl Nickel), BKAB (Antique Brass), BKSB, PWSB (Satin Brass), BKBS, PWBS (Brushed Steel) or BKSS, PWSS (Stainless Steel)
Dimensions	Module Width: 24.5mm, Module Height: 50mm Aperture Width: 20mm, Aperture Height: 35mm
Material composition	Rocker: Urea or Urea + Stainless Steel Cover (Ingot) Cover, Insert & Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Voltage	250V~ 50Hz
Current Rating	20AX (Suitable for inductive loads)
Terminal Size	5mm Diameter
Torque Value	1.2Nm
Cable Size	2 x 4mm ² , 3 x 2.5mm ² or 1 x 6mm ²
Back Box Depth	25mm – 47mm (Deco, Deco+, Mode, Polar) 35mm – 47mm (Define, Definity)
Operational Temperature	-5°C – +40°C
Warranty	10 Years

Standards	BS EN 60669-1
-----------	---------------

Additional Information	<p>Key Supplied (MI003 - Spare Key)</p> <p>Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.</p> <p>These products are rated at 20AX; therefore all terminals should not exceed the stated amperage.</p> <p>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.</p>
------------------------	--

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0