

## SPECIFICATION SHEET

**Product Code** CPC036N++

**Product Description** 13A 2 Gang DP Switched UK Socket With Neon


### General Information

Dimensions	146mm x 86mm x 27.5mm
Finishes Available	CPC036N: White, CPC036NSV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate & Neon Lens: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	120.6mm
Terminal Screw Size	4mmø
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup> , 1 x 6mm <sup>2</sup>
Switched	Yes
Double Pole	Yes
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

### Standards

BS 1363-2: 2016

### Additional Information

Ensure that the mains supply is isolated before commencing installation.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.