

## SPECIFICATION SHEET

**Product Code**

CPC202++

**Product Description**

45A DP 2 Gang (Vertical) Plate Switch


**General Information**

Dimensions	86mm x 146mm x 47.5mm
Finishes Available	CPC202: White, CPC202SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	45A
Fixing Centres	120.6mm (Vertical Fixing)
Terminal Screw Size	6mmø
Terminal Torque	2.5Nm
Terminal Capacity	16mm <sup>2</sup> Max.
Switched	Yes
Double Pole	Yes
Twin Earth	Yes
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

**Standards**

BS EN 60669- 1: 1999 + A1: 2002 + A2: 2008

**Additional Information**

Ensure that the mains supply is isolated before commencing installation.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.