

SPECIFICATION SHEET

Product Code

CPC651++

Product Description

13A Fused Connection Unit Switched


General Information

Dimensions	86mm x 86mm x 23.5mm
Finishes Available	CPC651: White, CPC651SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate & Fuse Drawer: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	60.3mm
Terminal Screw Size	4mmø
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm ² , 2 x 4mm ² , 1 x 6mm ²
Switched	Yes
Double Pole	Yes
Flex Outlet	No
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

Standards

BS 1363-4: 2016

Additional Information

Ensure that the mains supply is isolated before commencing installation.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.