

SPECIFICATION SHEET

Product Code CPC232NAC++

Product Description 32A DP 1 Gang Plate Switch With Neon Air Conditioning


General Information

Dimensions	86mm x 86mm x 31.5mm
Finishes Available	CPC232NAC: White, CPC232NACSV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate & Neon Lens: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	32A
Fixing Centres	60.3mm
Terminal Screw Size	6mmø
Terminal Torque	2.5Nm
Terminal Capacity	16mm ² Max.
Switched	Yes
Double Pole	Yes
Twin Earth	Yes
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

Standards

BS EN 60669- 1: 1999 + A1: 2002 + A2: 2008

Additional Information

Ensure that the mains supply is isolated before commencing installation.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.