

## SPECIFICATION SHEET

**Product Code**

CPC050++

**Product Description**

13A Fused Connection Unit With Flex Outlet


**General Information**

Dimensions	86mm x 86mm x 23.5mm
Finishes Available	CPC050: White, CPC050SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate & Fuse Drawer: Polycarbonate Insert & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	60.3mm
Terminal Screw Size	4mmØ
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup> , 1 x 6mm <sup>2</sup>
Switched	No
Flex Outlet	Yes
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

**Standards**

BS 1363-4: 2016

**Additional Information**

Ensure that the mains supply is isolated before commencing installation.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.