

## SPECIFICATION SHEET

**Product Code** CPC9835N++**Product Description** 1 Gang 13A Universal Switched Socket With Neon**General Information**

|                      |  |
|----------------------|--|
| Dimensions           | 86mm x 86mm x 27.5mm   |
| Finishes Available   | CPC9835N: White, CPC9835NSV: Silver (RAL 9006 (White Aluminium))   |
| Material Composition | Front Plate & Neon Lens: Polycarbonate<br>Insert, Switch & Base: Polycarbonate<br>Terminals: Brass Plated Steel<br>Terminal Screws: Steel and Yellow Passivated<br>Internal Busbars: Formed Pressed Brass<br>Silver "On-lay" Copper/Brass Contacts |
| Maximum Voltage      | 250V~ 50Hz   |
| Current Rating       | 13A  |
| Fixing Centres       | 60.3mm   |
| Terminal Screw Size  | 4mmø   |
| Terminal Torque      | 1.2Nm  |
| Terminal Capacity    | 3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup> , 1 x 6mm <sup>2</sup>   |
| Switched             | Yes  |
| Double Pole          | No   |
| Back Box Depth       | 35mm Minimum   |
| Temperature Rating   | -5° to +40°C   |
| Warranty             | 10 Years (Domestic)  |

**Additional Information**

Ensure that the mains supply is isolated before commencing installation.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

**Plug Compatibility**

13A British Standard, 5A Round Pin, 2A Round Pin  
16A European Schuko, 2.5A European 2 Pin Flat,  
US 3 Pin, 10A Australian 3 Pin, 10A Chinese 3 Pin